



NOTES:

1. MATERIAL
 - 1.1 CABLE: {[(7/0.12 BARE COPPER + PVC), SPIRAL (28/0.1 BARE COPPER) SHIELDED] X 6COAX + [(7/0.12 BARE COPPER X 4C, AL-FOIL SHIELEDE WITH A DRAIN)]}, AL-FOIL SHIELEDE WITH A DRAIN WIRE(7/0.16 TINNED COPPER), RED PVC JACKET. OD=ø10.5 ± 0.3mm
 - 1.2 CN1 & CN2: 21 PIN SCART MALE, CRIMPING TYPE, BLACK INSULATION, GOLD PLATED CONTACTS AND SHELL.
 - 1.3 SCART HOOD, NICKEL PLATED PLASTIC ASSEMBLY HOOD.
2. TESTING: 100% OPEN AND SHORT AND MISWIRE TEST.
3. EACH CABLE IN BLISTER WITH PAPER CARD.

P/N CHART

P/N.	L (mm)	T (mm)
147750	5000	+152/-51
147730	3000	+152/-51
147715	1500	+152/-51
147707	750	+50/-50

	mm
SCALE	NONE
SHEET	1/1
DIMENSIONAL TOLERANCES UNLESS OTHERWISE NOTED	
.X ±0.3	.XX ±
.XXX ±	ANGLES ±
REV. 00	CUS. REV.



SCART M to SCART M